

DOOR - VARIES BY PROJECT - PROVIDE FULL WEATHER SEALS / SWEEPS ETC. - DOOR MUST BE INSTALLED ON THE EXTERIOR SIDE OF THE FRAME

PREFINISHED, FRY 2-PIECE, "STUCCO REGLET STX" AND COUNTERFLASHING (OR APPROVED EQUAL) - BEND VERT. LEG OF REGLET TO RUN HORIZONTALLY OVER TOP OF WALL AS SHOWN - SPACE BETWEEN REGLET AND DOOR FRAME TO BE AS MINIMAL AS POSSIBLE - SEAL JOINT BETWEEN REGLET AND DOOR FRAME

PRE-FINISHED, 24 GA. G.I. TWO PIECE COUNTER-FLASHING AND REGLET W/ GASKETED FASTENERS @ 12" O.C.

TERMINATION BAR AT TOP OF SPM FLASHING MEMBRANE - PROVIDE COMPATIBLE SEALANT BEHIND MEMBRANE AND OVER TOP OF TERMINATION BAR - FASTENER LENGTH AS REQ'D. FASTEN TO WALL / FRAMING

WALL - TYPE VARIES BY PROJECT

SINGLE PLY ROOFING SYSTEM - VARIES PER PROJECT

WALK PAD

AIR & MOISTURE BARRIER

VAPOR RETARDER AS REQ'D.

DECK AS OCCURS - VARIES PER PROJECT

4-SIDED HOLLOW METAL FRAME WITH ALL JOINTS WELDED

ADHERE WALK PAD MATERIAL TO SILL OF DOOR FRAME

SEAL AROUND ENTIRE PERIMETER OF FRAME (BOTH SIDES)

1'-0" MIN.

8" MIN.

DOOR SILL @ ROOF